

DC/AC Inverter

1000~3000W True Sine Wave



▲ TS-1000 345x 184x 70 mm

▲ TS-1500 420x 220x 88 mm

▲ TS-2200 / 3000 474x 283x 98 mm

Features

- True sine wave output (THD<3%)
- 2 times high surge power for motor related application
- Advanced digital control by microprocessor
- High efficiency up to 93%
- Standby saving mode to conserve energy
- Built-in fan ON/OFF control function
- Output voltage / frequency adjustable
- Front panel indicator for load / battery / operation status
- High frequency design
- Input protections:
Bat. low alarm / Bat. low shutdown / reverse polarity / over voltage
- Output protections:
Short circuit / Overload / Over temperature
- Applications:
Home appliance, power tools, office and portable equipment, vehicle and yacht...etc.
- 2 years warranty

General Specification (Please refer to www.meanwell.com for detail spec.)



Model Name	TS-1000	TS-1500	TS-2200 Under Development	TS-3000 Under Development
Rated output power	1000W	1500W	2200W	3000W
Maximum output power	1150W for 3 minutes; 1500W for 10 sec.	1725W for 3 minutes ; 2250W for 10 sec.	2530W for 3 minutes ; 3300W for 10 sec	3450W for 3 minutes ; 4500W for 10 sec.
Output surge rating (30 cycles.)	2000W	3000W	4400W	6000W
DC input rated voltage	12VDC, 24VDC or 48VDC			
AC output voltage	100 / 110 / 115 / 120VAC or 200 / 220 / 230 / 240VAC selectable by setting button			
Output frequency	50Hz/60Hz selectable by setting button			
AC output waveform	True sine wave, THD<3.0%			
AC output regulation	±3% of rated output voltage			
No load dissipation	≤6W @ standby saving mode	≤18W @ standby saving mode	≤7W @ standby saving mode	
Working temperature	0 ~ +40°C @ 100% load, 60°C @ 50% load			
Safety standards	110V	Compliance to UL458 (except for 48V and only for GFCI receptacle), TS-2200/3000 pending		
	230V	Compliance to EN60950-1		
EMC standards	110V	Compliance to FCC class A		
	230V	Compliance to EN55022 class A, E-Mark, EN61000-4-2,3,8, ENV50204		

1000W

Model Name	Continue power	Input VDC	Output VAC / Hz	Output socket	Effi.
TS-1000-112 A	1000W	10.5-15	110 / 60	TYPE-A	88%
TS-1000-124 A	1000W	21.0-30	110 / 60	TYPE-A	89%
TS-1000-148 A	1000W	42.0-60	110 / 60	TYPE-A	90%
TS-1000-212 B	1000W	10.5-15	230 / 50	TYPE-B	90%
TS-1000-224 B	1000W	21.0-30	230 / 50	TYPE-B	91%
TS-1000-248 B	1000W	42.0-60	230 / 50	TYPE-B	92%

□ = A, B (standard model), C, D, E or F (optional model)

2200W

Under Development

Model Name	Continue power	Input VDC	Output VAC / Hz	Output socket	Effi.
TS-2200-112 A	2200W	10.5-15	110 / 60	TYPE-A	87%
TS-2200-124 A	2200W	21.0-30	110 / 60	TYPE-A	89%
TS-2200-148 A	2200W	42.0-60	110 / 60	TYPE-A	90%
TS-2200-212 B	2200W	10.5-15	230 / 50	TYPE-B	88%
TS-2200-224 B	2200W	21.0-30	230 / 50	TYPE-B	90%
TS-2200-248 B	2200W	42.0-60	230 / 50	TYPE-B	93%

□ = A, B (standard model), C, D, E or F (optional model)

1500W

Model Name	Continue power	Input VDC	Output VAC / Hz	Output socket	Effi.
TS-1500-112 A	1500W	10.5-15	110 / 60	TYPE-A	87%
TS-1500-124 A	1500W	21.0-30	110 / 60	TYPE-A	89%
TS-1500-148 A	1500W	42.0-60	110 / 60	TYPE-A	90%
TS-1500-212 B	1500W	10.5-15	230 / 50	TYPE-B	88%
TS-1500-224 B	1500W	21.0-30	230 / 50	TYPE-B	90%
TS-1500-248 B	1500W	42.0-60	230 / 50	TYPE-B	91%

□ = A, B (standard model), C, D, E or F (optional model)

3000W

Under Development

Model Name	Continue power	Input VDC	Output VAC / Hz	Output socket	Effi.
TS-3000-112 A	2700W	10.5-15	110 / 60	TYPE-A	87%
TS-3000-124 A	3000W	21.0-30	110 / 60	TYPE-A	89%
TS-3000-148 A	3000W	42.0-60	110 / 60	TYPE-A	90%
TS-3000-212 B	3000W	10.5-15	230 / 50	TYPE-B	88%
TS-3000-224 B	3000W	21.0-30	230 / 50	TYPE-B	90%
TS-3000-248 B	3000W	42.0-60	230 / 50	TYPE-B	93%

□ = A, B (standard model), C, D, E or F (optional model)